

GIPIEMME - data 22-07-2012				Modello Ruota / Wheel model			
wheel technical specifications:				Tecno 155 Equipe			
Scheda Tecnica Ruota modello:				RACE 28"-700C old130 SH.+Camp.			
Made in Italy - Produzione Italiana				#			
Sizes	MISURE	Tyre	COPERTURA	1	Clincher	Copertoncino	
		Size	MISURA	2	28" - 700C		
		Etrto	ETRTO	3	ETRTO 622 - 13,5 DIN		
REAR Wheel - RIGHT side	POSTERIOR E LATO DX	Spokes No.	Q.TA' RAGGI	4	10		
		Spokes Length	LUNGH. RAGGI	5	L286		
		Spokes Crossing	TIPO INCROCIO	6	Cross x 2 (Inner/Outer overlapping)	Inc. x 2 (Int./Est. a contatto)	
		Spokes Tension Kg.	TENSIONE IN KG.	7	140 ± 8%		
REAR Wheel - LEFT side	POSTERIOR E LATO SX	Spokes No.	Q.TA' RAGGI	8	10		
		Spokes Length	LUNGH. RAGGI	9	L275 (+1)		
		Spokes Crossing	TIPO INCROCIO	10	Cross x 1 (Inner/Outer not overlapping)	Inc. x 1 (Int./Est. non a contatto)	
		Spokes Tension Kg.	TENSIONE IN KG.	11	85 ± 8%		
FRONT Wheel - RIGHT side	ANTERIORE LATO DX	Spokes No.	Q.TA' RAGGI	12	10		
		Spokes Length	LUNGH. RAGGI	13	L275		
		Spokes Crossing	TIPO INCROCIO	14	radial	radiale	
		Spokes Tension Kg.	TENSIONE IN KG.	15	105 ± 8%		
FRONT Wheel - LEFT side	ANTERIORE LATO SX	Spokes No.	Q.TA' RAGGI	16	10		
		Spokes Length	LUNGH. RAGGI	17	L275		
		Spokes Crossing	TIPO INCROCIO	18	radial	radiale	
		Spokes Tension Kg.	TENSIONE IN KG.	19	105 ± 8%		
Spokes & Nipples Specifications	SPECIFICHE RAGGI NIPLES ALTRO	Brand and type	Marca e tipo		Sapim LEADER		
		Spokes Material	Materiale Raggi		Stainless steel Inox	Acciaio Inox	
		Spokes Type	TIPO RAGGI	20	round Ø2mm	Tondi Ø2mm	
		Spokes Colour	COLORE RAGGI	21	black	nero	
		Nipples Type	TIPO NIPLES	22		ACI ABS L15 T.E.	
		Nipples Material	MATER.-COLORE Nipples	23	Ottone Nichelato	Brass Nichel	
		Washer	PIASTRINA/ROSETTA	24		- Ø 7 /4,4x0.5 INOX	
		Cross spokes	INCROCIO RAGGI	25	-	-	
		Nipples Stopper	FRENA FILETTI	25		NO liquid ->(autolock Nipples)	
RIMS Specifications	SPECIFICHE CERCHIO	Rim Material	MATERIALE	26	AL 6062 T6		
		Rim Sizes	TIPO PROFILO	27	H30,5 X18/13,5 welded, diamond-cut (saldato, diamantato)		
		Rim Colour	COLORE CERCHIO	28	Paint Black / White	Verniciato Nero/Bianco	
		Ø Valve Hole	Ø FORO VALVOLA	29	Ø 6,5 inner//outer	Ø 6,5 interno//esterno	
		Eyelets	BOCCOLE	31	No	No	
		Decoration	DECORAZIONI	32	Sticker	Etichette	
HUBS Specifications	SPECIFICHE MOZZO E CUSCINETTI	Front Hub	MOZZO ANT.	33	FRONT GPMJ20		
		Rear Hub SH.	MOZZO POST. SH.	34	REAR SH GPMJSH20		
		Rear Hub Campy	MOZZO POST. C.	35	REAR CAMP GPMJCA20		
		Q.L.D. Front/Rear Axle	INTERASSE BATTUTA	36	100/130 mm.		
		Spokes Holes Front/rear	FORI POST./ANT.	37	20/20 (std)		
		Hub Colour	COLORE MOZZO	38	BLACK		
		Front Hub Motion	CUSCINETTI 2RS ANT.	39	N.2 Ø26/10X8		
		Rear Hub Motion	CUSCINETTI 2RS POST.	40	N.2 Ø28/12X8		
SHIMANO cassette body	CASSETTE SHIMANO-CUSCINETTI-GHIERE	Material	MATERIALE	41	Ergal anod. Silver	Ergal anod. Silver	
		Shimano	SHIMANO	42	8/9/10S 12/11 teeth	8/9/10S 12/11 denti	
		Cassette Motion	CUSCINETTI 2RS	43	N.2 Ø15/28X7		
		Cog - 12	GHIERA 12 DENTI	44	std Shimano		
		Cog - 11	GHIERA 11 DENTI	45	std Shimano		
		Tightness Torque in Nm	SERRAGGIO GHIERA	46	35/45 Nm		
CAMPY cassette body	CASSETTE CAMPAGNOLO-CUSCINETTI-GHIERE	Material	MATERIALE	48	Ergal anod. Silver	Ergal anod. Silver	
		Campy	CAMPAGNOLO	49	9/10S/11S 12/11 teeth	9/10S/11S 12/11 denti	
		Cassette Seal Ball Bearings	CUSCINETTI 2RS	50	N.2 Ø 12 / 26 X 8		
		Cog - 12	GHIERA 12 DENTI	51	M27x1 Ø38		
		Cog - 11	GHIERA 11 DENTI	52	M27x1 Ø35		
		Tightness Torque in NM	COPPIA SERRAGGIO	53	35/45 Nm		
Cassette Body	CAMBIO CASSETTA	From Campy to SH.	da Campagnolo a SH.	54	Yes	Si	
		From SH. to Campy	da SH. a Campagnolo	55	Yes	Si	
Quick Release	BLOCCAGGI	Q.L.D.	INTERASSE CHIUSURA	56	100/130		
		Colour	COLORE	57	Black		
		Model	MODELLO	58	Light Race C		
		Weight	PESO	59	112 gr.		
WHEELS WEIGHT	PESO RUOTE	Front Wheel	RUOTA ANT. Gr.	60	74.4		
		Rear Wheel	RUOTA POST. GR.	61	921		
		Wheel SET ± 5%	COPPIA RUOTE GR. ±5%	62	1665		
ASSEMBLY TOLLERANCE	TOLLERANZ E RUOTE Anteriore	Max Roundness	Salto Max	63	0,30 mm.		
		Max obbling	Sbandamento Max	64	0,30 mm.		
		Max Symmetry	Campanatura Max	65	0,50 mm.		
Reccomended assembly	RACCOMAN DAZIONI D'USO	Reccomended Tyre	COPERTURA SUGGERITA	72	19 ± 25		
		Rim tape - Flap	NASTRO - FLAP	73	622 x 16 x 0,6		
		Max Inflate (Bars)	MAX PRES. CONSENTITA	74	Tyre/Copert. 19 ► 10 Bar - Tyre/Copert. 25 ► 9 Bar		
		Braking pads	PATTINI FRENO	75	standard		