

| GIPIEMME made in italy - www.gipiemme.com Rev. 22- | | | | wheel model Modello Ruota | |
|--|--|-----------------------------|--------------------------|------------------------------|---|
| 01-2010 | | | | | |
| wheel technical specifications: Scheda Tecnica Ruota modello: | | | | # | CARBON H 6.0 lighth da 28"-700C old130 SH.+Camp. |
| Sizes | MISURE | Tyre | COPERTURA | 1 | Tubular Tubolare |
| | | Size | MISURA | 3 | 28" - 700C |
| | | Etrto | ETRTO | 4 | ETRTO 632 - 20 DIN |
| | | | | | |
| REAR Wheel - RIGHT side | POSTERIORE LATO DX | Spokes Ng. | Q.TA' RAGGI | 4 | 10 |
| | | Spokes Lenght | LUNGH. RAGGI | 5 | L 258 |
| | | Spokes Crossing | TIPO INCROCIO | 6 | Cross x 2 (Inner/Outer overlapping) Inc. x 2 (Inf./Est. a contatto) |
| | | Spokes Tension Kg. | TENSIONE IN KG. | 7 | 140 ± 8% |
| REAR Wheel - LEFT side | POSTERIORE LATO SX | Spokes Ng. | Q.TA' RAGGI | 8 | 10 |
| | | Spokes Lenght | LUNGH. RAGGI | 9 | L258 |
| | | Spokes Crossing | TIPO INCROCIO | 10 | Cross x 2 (Inner/Outer overlapping) Inc. x 2 (Inf./Est. a contatto) |
| | | Spokes Tension Kg. | TENSIONE IN KG. | 11 | 85 ± 8% |
| FRONT Wheel - RIGHT side | ANTERIORE LATO DX | Spokes Ng. | Q.TA' RAGGI | 12 | 10 |
| | | Spokes Lenght | LUNGH. RAGGI | 13 | L250 |
| | | Spokes Crossing | TIPO INCROCIO | 14 | Radial (inner) - radiali (int.) |
| | | Spokes Tension Kg. | TENSIONE IN KG. | 15 | 105 ± 8% |
| FRONT Wheel - LEFT side | ANTERIORE LATO SX | Spokes Ng. | Q.TA' RAGGI | 16 | 10 |
| | | Spokes Lenght | LUNGH. RAGGI | 17 | L250 |
| | | Spokes Crossing | TIPO INCROCIO | 18 | Radial (inner) - radiali (int.) |
| | | Spokes Tension Kg. | TENSIONE IN KG. | 19 | 105 ± 8% |
| Spokes & Nipples Specifications | SPECIFICHE RAGGI NIPLES ALTRO | Brand and type | Marca e tipo | | Sapim CX-Ray |
| | | Spokes Material | Materiale Raggi | | Stainless steel Inox Acciaio Inox |
| | | Spokes Type | TIPO RAGGI INOX | 20 | Aerodynamic Ø 2 with reduced section aerodinamico Ø 2 con sezione ridotta |
| | | Spokes Colour | COLORE RAGGI | 21 | black nero |
| | | Nipples Type | TIPO NIPLES | 22 | ACI ABS ERGAL L15 T.E. |
| | | Nipples Material | MATERIALE-COLORE Nipples | 23 | Ergal Red Ergal ROSSO |
| | | Washer | PIASTRINA/ROSETTA | 24 | ottone - Ø 8 /4,5x 1 |
| | | Nipples Stopper | FRENA FILETTI | 25 | NO (autolock Nipples) |
| RIMS Specifications | SPECIFICHE CERCHIO | Rim Material | MATERIALE | 26 | carbonio 100% carbonio 100% |
| | | Rim Sizes | TIPO PROFILO | 27 | H 60 X 20 diamond-cut (diamantato) |
| | | Rim Colour | COLORE CERCHIO | 28 | black carbon nero carbonio |
| | | Ø Valve Hole | Ø FORO VALVOLA | 29 | Ø 6,5 inner//outer Ø 6,5 interno//esterno |
| | | Eyelets | BOCCOLE | 31 | No No |
| | | Decoration | DECORAZIONI | 32 | Sticker Etichette |
| HUBS Specifications | SPECIFICHE MOZZO E CUSCINETTI | Front Hub | MOZZO ANT. | 33 | FRONT LIGHT C-H-2 |
| | | Rear Hub SH. | MOZZO POST. SH. | 34 | REAR SH LIGHT C-H-2 |
| | | Rear Hub Campy | MOZZO POST. C. | 35 | REAR CAMP LIGHT C-H-2 |
| | | O.L.D. Front/Rear Axle | INTERASSE BATTUTA | 36 | 100/130 mm. |
| | | Spokes Holes Front/rear | FORI POST./ANT. | 37 | 20/20 (std) |
| | | Hub Colour | COLORE MOZZO | 38 | BLACK |
| | | Front Hub Motion | CUSCINETTI 2RS ANT. | 39 | N.2 Ø10/22x6 |
| | | Rear Hub Motion | CUSCINETTI 2RS POST. | 40 | N.2 Ø15/28x7 |
| SHIMANO cassette body | CASSETTE SHIMANO- CUSCINETTI- GHIERE | Material | MATERIALE | 41 | Ergal anod. Silver Ergal anod. Silver |
| | | Shimano | SHIMANO | 42 | 8/9/10S 12/11 teeth 8/9/10S 12/11 denti |
| | | Cassette Motion | CUSCINETTI 2RS | 43 | N.2 Ø15/28X7 |
| | | Cog - 12 | GHIERA 12 DENTI | 44 | std Shimano |
| | | Cog - 11 | GHIERA 11 DENTI | 45 | std Shimano |
| | | Thightness Torque in Nm | SERRAGGIO GHIERA | 46 | 35/45 Nm |
| CAMPY cassette body | CASSETTE CAMPAGNOLO- CUSCINETTI- GHIERE | Material | MATERIALE | 48 | Ergal anod. Silver Ergal anod. Silver |
| | | Campy | CAMPAGNOLO | 49 | 9/10S 12/11 teeth 9/10S 12/11 denti |
| | | Cassette Seal Ball Bearings | CUSCINETTI 2RS | 50 | N.2 Ø15/24X5 |
| | | Cog - 12 | GHIERA 12 DENTI | 51 | M27x1 Ø38 |
| | | Cog - 11 | GHIERA 11 DENTI | 52 | M27x1 Ø35 |
| | | Thightness Torque in NM | COPPIA SERRAGGIO | 53 | 35/45 Nm |
| Cassette Body replacement | CAMBIO CASSETTA | From Campy to SH. | da Campagnolo a SH. | 54 | Yes Si |
| | | From SH. to Campy | da SH. a Campagnolo | 55 | Yes Si |
| Quick Release | BLOCCAGGI | O.L.D. | INTERASSE CHIUSURA | 56 | 100/130 |
| | | Colour | COLORE | 57 | BLACK |
| | | Model | MODELLO | 58 | Light Race C |
| | | Weight | PESO | 59 | 112 gr. |
| WHEELS WEIGHT | PESO RUOTE | Front Wheel | RUOTA ANT. Gr. | 60 | 640 |
| | | Rear Wheel | RUOTA POST. GR. | 61 | 820 |
| | | Wheel SET ± 5% | COPPIA RUOTE GR. ± 5% | 62 | 1460 |
| ASSEMBLYING TOLLERANCE FRONT & REAR | TOLLERANZE RUOTE Anteriore & | Max Roundness | Salto Max | 63 | 0,30 mm. |
| | | Max obbling | Sbandamento Max | 64 | 0,30 mm. |
| | | Max Simmetry | Campanatura Max | 65 | 0,50 mm. |
| Recommened assembly | RACCOMANDAZIO NI D'USO | Recommened Tyre | COPERTURA SUGGERITA | 72 | 19 ± 25 |
| | | Rim tape - Flap | NASTRO - FLAP | 73 | ----- |
| | | Max Inflate (Bars) | MAX PRES. CONSENTITA | 74 | specified Tyre specifiche copertura |
| | | Braking pads | PATTINI FRENO | 75 | special for carbon speciale per carbonio |