

GIPIEMME - data 29-05-2011				Modello Ruota / Wheel model			
wheel technical specifications:				KENYA 27.5" 32 RAGGI TUBELESS			
Scheda Tecnica Ruota modello:				etrto -584-17 din old135			
Made in Italy - Produzione Italiana				#			
SIZES	MISURE	Tyre	COPERTURA	1	Clincher / Tubeless	Copertoncino / Tubeless	
		Size	MISURA	2	27,5" - mtb		
		Etrto	ETRTO	3	ETRTO 584- 17 DIN		
REAR Wheel - RIGHT side	POSTERIORE LATO DX	Spokes No.	Q.TA' RAGGI	4	16		
		Spokes Length	LUNGH. RAGGI	5	L 276		
		Spokes Crossing	TIPO INCROCIO	6	Cross x 3 (Inner/Outer overlapping)	Inc. x 3 (Inf./Est. a contatto)	
		Spokes Tension Kg.	TENSIONE IN KG.	7	125 ± 8%		
REAR Wheel - LEFT side	POSTERIORE LATO SX	Spokes No.	Q.TA' RAGGI	8	16		
		Spokes Length	LUNGH. RAGGI	9	L 278		
		Spokes Crossing	TIPO INCROCIO	10	Cross x 3 (Inner/Outer overlapping)	Inc. x 3 (Inf./Est. a contatto)	
		Spokes Tension Kg.	TENSIONE IN KG.	11	85 ± 8%		
FRONT Wheel - RIGHT side	ANTERIORE LATO DX	Spokes No.	Q.TA' RAGGI	12	16		
		Spokes Length	LUNGH. RAGGI	13	L 280		
		Spokes Crossing	TIPO INCROCIO	14	Cross x 3 (Inner/Outer overlapping)	Inc. x 3 (Inf./Est. a contatto)	
		Spokes Tension Kg.	TENSIONE IN KG.	15	100 ± 8%		
FRONT Wheel - LEFT side	ANTERIORE LATO SX	Spokes No.	Q.TA' RAGGI	16	16		
		Spokes Length	LUNGH. RAGGI	17	L 276		
		Spokes Crossing	TIPO INCROCIO	18	Cross x 3 (Inner/Outer overlapping)	Inc. x 3 (Inf./Est. a contatto)	
		Spokes Tension Kg.	TENSIONE IN KG.	19	100 ± 8%		
		Brand and type	MARCA E TIPO		Sapim Leader		
		Spokes Material	MATERIALE RAGGI		Stainless steel Inox 18/8	Acciaio Inox 18/8	
Spokes & Nipples Specifications	SPECIFICHE RAGGI NIPLES ALTRO	Spokes Type	TIPO RAGGI INOX	20	ROUND Ø 2	TONDO Ø 2	
		Spokes Colour	COLORE RAGGI	21	black	nero	
		Nipples Type	TIPO NIPLES	22	ACI ABS L15 T.E.		
		Nipples Material	MATERIALE-COLORE Nipples	23	OTTONE / BRASS		
		Washer	PIASTRINA/ROSETTA	24	RONDELLE OTTONE		
		Cross spokes	INCROCIO RAGGI	25	////////	////////	
		Nipples Stopper	FRENA FILETTI	26	NO (autolock Nipples)		
RIMS Specifications	SPECIFICHE CERCHIO	Rim Material	MATERIALE	27	AL 6082 T6		
		Rim Sizes	TIPO PROFILO	28	H 20 X 23 Welded (Saldata) DIAM. 597 - ETRTO 584		
		Rim Colour	COLORE CERCHIO	29	Anodiz. Black	Anodiz. Nero	
		Ø Valve Hole	Ø FORO VALVOLA	30	Ø 6,5 inner//outer	Ø 6,5 interno/esterno	
		Eyelets	BOCCOLE	31	yes	si	
		Decoration	DECORAZIONI	32	Laser + Sticker	Laser + Etichette	
HUBS Specifications	SPECIFICHE MOZZO E CUSCINETTI	Front Hub	MOZZO ANT.	33	LIGHT DISC FC-H-1		
		Rear Hub SH.	MOZZO POST. SH.	34	LIGHT DISC RC-H-1		
		O.L.D. Front/Rear Axle	INTERASSE BATTUTA	36	100/135 mm.		
		Spokes Holes Front/rear	FORI POST./ANT.	37	32/32 (std)		
		Hub Colour	COLORE MOZZO	38	BLACK	NERO	
		Front Hub Motion	CUSCINETTI 2RS ANT.	39	N.2 Ø 10 / 26 x 8		
		Rear Hub Motion	CUSCINETTI 2RS POST.	40	N. 2 Ø 15 / 28 x 7		
SHIMANO cassette body	CASSETTE SHIMANO-CUSCINETTI-GHIERE	Material	MATERIALE	41	Ergal anodized	Ergal anodizzato	
		Shimano	SHIMANO	42	8/9/10S 12/11 teeth	8/9/10S 12/11 denti	
		Cassette Motion	CUSCINETTI 2RS	43	N.2 Ø15/28X7		
		Cog - 12	GHIERA 12 DENTI	44	std Shimano		
		Cog - 11	GHIERA 11 DENTI	45	std Shimano		
		Thightness Torque in Nm	SERRAGGIO GHIERA	46	35/45 Nm		
Quick Release	BLOCCAGGI	O.L.D.	INTERASSE CHIUSURA	56	100/135		
		Colour	COLORE	57	Black		
		Model	MODELLO	58	Light Mtb k		
		Weight	PESO	59	gr. 114		
WHEELS WEIGHT	PESO RUOTE	Front Wheel	RUOTA ANT. Gr.	60	820		
		Rear Wheel	RUOTA POST. GR.	61	961		
		Wheel SET ± 5%	COPPIA RUOTE GR. ± 5%	62	1781		
ASSEMBLYING TOLLERANCE FRONT & REAR	TOLLERANZE RUOTE Anteriore &	Max Roundness	Salto Max	63	0,30 mm.		
		Max obbling	Sbandamento Max	64	0,30 mm.		
		Max Simmetry	Campanatura Max	65	0,50 mm.		