

wheel technical specifications:

Scheda Tecnica Ruota modello:

PISTA A40 colori vari

TRACK 28"-700C cop. Old120/100

				#			
Sizes	MISURE	Tyre	COPERTURA	1	Clincher	Copertoncino	
		Size	MISURA	2	28" - 700C		
		Etrto	ETRTO	3	ETRTO 622 - 13.5 DIN		
REAR Wheel RIGHT side	POSTERIORE LATO DX	Spokes No.	Q.TA' RAGGI	4	16		
		Spokes Lenght	LUNGH. RAGGI	5	270		
		Spokes Crossing	TIPO INCROCIO	6	Cross x 3 (Inner/Outer overlapping)	Inc. x 3 (Int./Est. a contatto)	
		Spokes Tension Kg.	TENSIONE IN KG.	7	130 ± 8%		
REAR Wheel LEFT side	POSTERIORE LATO SX	Spokes No.	Q.TA' RAGGI	8	16		
		Spokes Lenght	LUNGH. RAGGI	9	270		
		Spokes Crossing	TIPO INCROCIO	10	Cross x 3 (Inner/Outer overlapping)	Inc. x 3 (Int./Est. a contatto)	
		Spokes Tension Kg.	TENSIONE IN KG.	11	130 ± 8%		
FRONT Wheel RIGHT side	ANTERIORE LATO DX	Spokes No.	Q.TA' RAGGI	12	16		
		Spokes Lenght	LUNGH. RAGGI	13	248		
		Spokes Crossing	TIPO INCROCIO	14	RADIALE	RADIAL	
		Spokes Tension Kg.	TENSIONE IN KG.	15	130 ± 8%		
FRONT Wheel LEFT side	ANTERIORE LATO SX	Spokes No.	Q.TA' RAGGI	16	16		
		Spokes Lenght	LUNGH. RAGGI	17	248		
		Spokes Crossing	TIPO INCROCIO	18	RADIALE	RADIAL	
		Spokes Tension Kg.	TENSIONE IN KG.	19	130 ± 8%		
Spokes & Nipples Specifications	SPECIFICHE RAGGI NIPLES ALTRO	Spokes Type	TIPO RAGGI	20	ROUND Ø 2 inox	TONDO Ø 2 inox	
		Spokes Colour	COLORE RAGGI	21	silver		
		Nipples Type	TIPO NIPLES	22	ottone 12 mm		
		Nipples Material	MATERIALE-COLORE N	23	ottone nichelato		
		Washer	PIASTRINA/ROSETTA	24	no	no	
		Nipples Stopper	FRENA FILETTI	25	no		
RIMS Specifications	SPECIFICHE CERCHIO	Rim Material	MATERIALE	26	AL 6005 T6		
		Rim Sizes	TIPO PROFILO	27	H 40 X 19 / 13.5		
		Rim Colour	COLORE CERCHIO	28	Paint black / white / silver	verniciato nero / bianco / silver	
		Ø Valve Hole	Ø FORO VALVOLA	29	Ø 6.5 / 8.5		
		Rubber hole valve	GOMMINO FORO VALVOLA		no	no	
		Eyelets	BOCCOLE	31	no	no	
		Decoration	DECORAZIONI	32	Sticker 2 X edge	Etichette 2 per lato	
HUBS Specifications	SPECIFICHE MOZZO E CUSCINETTI	Front Hub	MOZZO ANT.	33	PISTA FRONT cuscinetti -32H		
		Rear Hub SH.	MOZZO POST. SH.	34	PISTA REAR cuscinetti -32H flip-flop		
		Q.L.D. Front/Rear A	INTERASSE BATTUTA	36	100/120 mm.		
		Spokes Holes Front/r	FORI POST./ANT.	37	32/32		
		Hub Colour	COLORE MOZZO	38	SILVER / NERO BLACK		
		Front Hub Motion	CUSCINETTI 2RS ANT.	39	N.2		
		Rear Hub Motion	CUSCINETTI 2RS POST	40	N.2		
WHEELS WEIGHT	PESO RUOTE	Front Wheel	RUOTA ANT. Gr.	60	1240		
		Rear Wheel	RUOTA POST. GR.	61	1290		
		Wheel SET ± 5%	COPPIA RUOTE GR. ±	62	2530		
ASSEMBLYING TOLLERANCE FRONT & REAR	TOLLERANZE RUOTE Anteriore &	Max Roundness	Salto Max	63	0,30 mm.		
		Max obbling	Sbandamento Max	64	0,30 mm.		
		Max Simmetry	Campanatura Max	65	0,50 mm.		
Reccomended assembly	RACCOMANDAZI ONI D'USO	Reccomended Tyre	COPERTURA SUGGERIT	72	19 + 25		
		Rim tape - Flap	NASTRO - FLAP	73	622 x 16 x 0,6		
		Max Inflate (Bars)	MAX PRES. CONSENTI	74	Tyre/Copert. 19 ▶ 10 Bar - Tyre/Copert. 25 ▶ 9 Bar		
		Braking pads	PATTINI FRENO	75	standard		