

GIPIEMME		made in italy -		wheel model	
www.gipiemme.com		03-09-2007		Modello Ruota	
wheel technical specifications: Scheda Tecnica Ruota modello:				#	SIERRA Tubular disc 26"-571 old135
Sizes	MISURE	Tyre	COPERTURA	1	Tubular Tubolare
		Size	MISURA	2	26" - mtb
		Etrto	ETRTO	3	ETRTO 571- 25 DIN
REAR Wheel - RIGHT side	POSTERIORE LATO DX	Spokes No.	Q.TA' RAGGI	4	12
		Spokes Length	LUNGH. RAGGI	5	L 242
		Spokes Crossing	TIPO INCROCIO	6	Cross x 2 (Inner/Outer overlapping) Inc. x 2 (Int./Est. a contatto)
		Spokes Tension Kg.	TENSIONE IN KG.	7	125 ± 8%
REAR Wheel - LEFT side	POSTERIORE LATO SX	Spokes No.	Q.TA' RAGGI	8	12
		Spokes Length	LUNGH. RAGGI	9	L 242
		Spokes Crossing	TIPO INCROCIO	10	Cross x 2 (Inner/Outer overlapping) Inc. x 2 (Int./Est. a contatto)
		Spokes Tension Kg.	TENSIONE IN KG.	11	85 ± 8%
FRONT Wheel - RIGHT side	ANTERIORE LATO DX	Spokes No.	Q.TA' RAGGI	12	12
		Spokes Length	LUNGH. RAGGI	13	L 245
		Spokes Crossing	TIPO INCROCIO	14	Cross x 2 (Inner/Outer overlapping) Inc. x 2 (Int./Est. a contatto)
		Spokes Tension Kg.	TENSIONE IN KG.	15	100 ± 8%
FRONT Wheel - LEFT side	ANTERIORE LATO SX	Spokes No.	Q.TA' RAGGI	16	12
		Spokes Length	LUNGH. RAGGI	17	L 240
		Spokes Crossing	TIPO INCROCIO	18	Cross x 2 (Inner/Outer overlapping) Inc. x 2 (Int./Est. a contatto)
		Spokes Tension Kg.	TENSIONE IN KG.	19	100 ± 8%
Spokes & Nipples Specifications	SPECIFICHE RAGGI NIPLES ALTRO	Spokes Type	TIPO RAGGI INOX	20	Aerodynamic Ø 2 with reduced section aerodinamico Ø 2 con sezione ridotta
		Spokes Colour	COLORE RAGGI	21	black nero
		Nipples Type	TIPO NIPLES	22	ACI ABS ERGAL L13 T.E.
		Nipples Material	MATERIALE-COLORE Nipples	23	Ergal Black
		Washer	PIASTRINA/ROSETTA	24	OVALE INOX
		Cross spokes	INCROCIO RAGGI	25	rubber isolation gommino isolante
Nipples Stopper	FRENA FILETTI	26	NO (autolock Nipples)		
RIMS Specifications	SPECIFICHE CERCHIO	Rim Material	MATERIALE	27	carbonio 100% carbon 100%
		Rim Sizes	TIPO PROFILO	28	H 40 X 25
		Rim Colour	COLORE CERCHIO	29	black carbon nero carbonio
		Ø Valve Hole	Ø FORO VALVOLA	30	Ø 6,5 inner//outer Ø 6,5 interno//esterno
		Eyelets	BOCCOLE	31	No No
		Decoration	DECORAZIONI	32	Sticker Etichette
HUBS Specifications	SPECIFICHE MOZZO E CUSCINETTI	Front Hub	MOZZO ANT.	33	LIGHT DISC RS 1700
		Rear Hub SH.	MOZZO POST. SH.	34	LIGHT DISC RS 1700
		O.L.D. Front/Rear Axle	INTERASSE BATTUTA	36	100/135 mm.
		Spokes Holes Front/rear	FORI POST./ANT.	37	24/24 (std)
		Hub Colour	COLORE MOZZO	38	BLACK NERO
		Front Hub Motion	CUSCINETTI 2RS ANT.	39	N.2 Ø 15 / 24 x 5
Rear Hub Motion	CUSCINETTI 2RS POST.	40	N. 2 Ø 15 / 26 x 7		
SHIMANO cassette body	CASSETTE SHIMANO-CUSCINETTI-GHIERE	Material	MATERIALE	41	Ergal anodized Ergal anodizzato
		Shimano	SHIMANO	42	8/9/10S 12/11 teeth 8/9/10S 12/11 denti
		Cassette Motion	CUSCINETTI 2RS	43	N.2 Ø 15 / 24 X 5
		Cog - 12	GHIERA 12 DENTI	44	std Shimano
		Cog - 11	GHIERA 11 DENTI	45	std Shimano
		Thightness Torque in Nm	SERRAGGIO GHIERA	46	35/45 Nm
Quick Release	BLOCCAGGI	O.L.D.	INTERASSE CHIUSURA	56	100/135
		Colour	COLORE	57	Black
		Model	MODELLO	58	Light MtB k
		Weight	PESO	59	gr. 114
WHEELS WEIGHT	PESO RUOTE	Front Wheel	RUOTA ANT. Gr.	60	573
		Rear Wheel	RUOTA POST. GR.	61	721
		Wheel SET ± 5%	COPPIA RUOTE GR. ± 5%	62	1294
ASSEMBLY TOLLERANCE FRONT & REAR	TOLLERANZE RUOTE Anteriore & Posteriore	Max Roundness	Salto Max	63	0,40 mm.
		Max obbling	Sbandamento Max	64	0,40 mm.
		Max Simmetry	Campanatura Max	65	0,50 mm.