

GIPIEMME - data 15-03-2012				Modello Ruota / Wheel model		
wheel technical specifications:				KENYA 27.5"32 RAGGI TUBOLARE		
Scheda Tecnica Ruota modello:				etrto -584-17 din old135		
Made in Italy - Produzione Italiana				#		
Sizes	MISURE	Tyre	COPERTURA	1	Tubular Tubolare	
		Size	MISURA	2	27,5" - mtb	
		Etrto	ETRTO	3	ETRTO 584- 17 DIN	
REAR Wheel - RIGHT side	POSTERIORE LATO DX	Spokes No.	Q.TA' RAGGI	4	16	
		Spokes Lenght	LUNGH. RAGGI	5	L 276	
		Spokes Crossing	TIPO INCROCIO	6	Cross x 3 (Inner/Outer overlapping) Inc. x 3 (Int./Est. a contatto)	
		Spokes Tension Kg.	TENSIONE IN KG.	7	125 ± 8%	
REAR Wheel - LEFT side	POSTERIORE LATO SX	Spokes No.	Q.TA' RAGGI	8	16	
		Spokes Lenght	LUNGH. RAGGI	9	L 278	
		Spokes Crossing	TIPO INCROCIO	10	Cross x 3 (Inner/Outer overlapping) Inc. x 3 (Int./Est. a contatto)	
		Spokes Tension Kg.	TENSIONE IN KG.	11	85 ± 8%	
FRONT Wheel - RIGHT side	ANTERIORE LATO DX	Spokes No.	Q.TA' RAGGI	12	16	
		Spokes Lenght	LUNGH. RAGGI	13	L 280	
		Spokes Crossing	TIPO INCROCIO	14	Cross x 3 (Inner/Outer overlapping) Inc. x 3 (Int./Est. a contatto)	
		Spokes Tension Kg.	TENSIONE IN KG.	15	100 ± 8%	
FRONT Wheel - LEFT side	ANTERIORE LATO SX	Spokes No.	Q.TA' RAGGI	16	16	
		Spokes Lenght	LUNGH. RAGGI	17	L 276	
		Spokes Crossing	TIPO INCROCIO	18	Cross x 3 (Inner/Outer overlapping) Inc. x 3 (Int./Est. a contatto)	
		Spokes Tension Kg.	TENSIONE IN KG.	19	100 ± 8%	
Spokes & Nipples Specifications	SPECIFICHE RAGGI NIPLES ALTRO	Brand and type	MARCA E TIPO		Sapim Leader	
		Spokes Material	MATERIALE RAGGI		Stainless steel Inox 18/8 Acciaio Inox 18/8	
		Spokes Type	TIPO RAGGI INOX	20	ROUND Ø 2	TONDO Ø 2
		Spokes Colour	COLORE RAGGI	21	black	nero
		Nipples Type	TIPO NIPLES	22	ACI ABS L15 T.E.	
		Nipples Material	MATERIALE-COLORE Nipples	23	OTTONE / BRASS	
		Washer	PIASTRINA/ROSETTA	24	RONDELLE OTTONE	
		Cross spokes	INCROCIO RAGGI	25	////////	////////
		Nipples Stopper	FRENA FILETTI	26	NO (autolock Nipples)	
		RIMS Specifications	SPECIFICHE CERCHIO	Rim Material	MATERIALE	27
Rim Sizes	TIPO PROFILO			28	H 20 X 23 Welded (Saldato) DIAM. 597 - ETRTO 584	
Rim Colour	COLORE CERCHIO			29	Anodiz. Black	Anodiz. Nero
Ø Valve Hole	Ø FORO VALVOLA			30	Ø 6,5 inner//outer	Ø 6,5 interno//esterno
Eyelets	BOCCOLE			31	yes	si
Decoration	DECORAZIONI			32	Laser + Sticker	Laser + Etichette
HUBS Specifications	SPECIFICHE MOZZO E CUSCINETTI			Front Hub	MOZZO ANT.	33
		Rear Hub SH.	MOZZO POST. SH.	34	LIGHT DISC RC-H-1	
		O.L.D. Front/Rear Axle	INTERASSE BATTUTA	36	100/135 mm.	
		Spokes Holes Front/rear	FORI POST./ANT.	37	32/32 (std)	
		Hub Colour	COLORE MOZZO	38	BLACK	NERO
		Front Hub Motion	CUSCINETTI 2RS ANT.	39	N.2 Ø 10 / 26 x 8	
		Rear Hub Motion	CUSCINETTI 2RS POST.	40	N. 2 Ø 15 / 28 x 7	
SHIMANO cassette body	CASSETTE SHIMANO-CUSCINETTI-GHIERE	Material	MATERIALE	41	Ergal anodized	Ergal anodizzato
		Shimano	SHIMANO	42	8/9/10S 12/11 teeth	8/9/10S 12/11 denti
		Cassette Motion	CUSCINETTI 2RS	43	N.2 Ø15/28X7	
		Cog - 12	GHIERA 12 DENTI	44	std Shimano	
		Cog - 11	GHIERA 11 DENTI	45	std Shimano	
		Thightness Torque in Nm	SERRAGGIO GHIERA	46	35/45 Nm	
Quick Release	BLOCCAGGI	O.L.D.	INTERASSE CHIUSURA	56	100/135	
		Colour	COLORE	57	Black	
		Model	MODELLO	58	Light MtB k	
		Weight	PESO	59	gr. 114	
WHEELS WEIGHT	PESO RUOTE	Front Wheel	RUOTA ANT. Gr.	60	813	
		Rear Wheel	RUOTA POST. GR.	61	961	
		Wheel SET ± 5%	COPPIA RUOTE GR. ± 5%	62	1774	
ASSEMBLYING TOLLERANCE FRONT & REAR	TOLLERANZE RUOTE Anteriore &	Max Roundness	Salto Max	63	0,30 mm.	
		Max obbling	Sbandamento Max	64	0,30 mm.	
		Max Simmetry	Campanatura Max	65	0,50 mm.	