

wheel technical specifications:

Scheda Tecnica Ruota modello:

#  
**Cyclocross H 4.0 Tubolare**  
da 28"-700C old130 SH.+Camp.

<b>Sizes</b>	<b>MISURE</b>	Tyre	COPERTURA	1	Tubular	Tubolare	
		Size	MISURA	3	28" - 700C		
		Etrto	ETRTO	4	ETRTO 632 - 22 DIN		
<b>REAR Wheel - RIGHT side</b>	<b>POSTERIORE LATO DX</b>	Spokes No.	Q.TA' RAGGI	4	10		
		Spokes Length	LUNGH. RAGGI	5	<b>L 276</b>		
		Spokes Crossing	TIPO INCROCIO	6	Cross x 2 (Inner/Outer overlapping)	Inc. x 2 (Int./Est. a contatto)	
		Spokes Tension Kg.	TENSIONE IN KG.	7	14.0 ± 8%		
<b>REAR Wheel - LEFT side</b>	<b>POSTERIORE LATO SX</b>	Spokes No.	Q.TA' RAGGI	8	10		
		Spokes Length	LUNGH. RAGGI	9	<b>L280</b>		
		Spokes Crossing	TIPO INCROCIO	10	Cross x 2 (Inner/Outer overlapping)	Inc. x 2 (Int./Est. a contatto)	
		Spokes Tension Kg.	TENSIONE IN KG.	11	85 ± 8%		
<b>FRONT Wheel - RIGHT side</b>	<b>ANTERIORE LATO DX</b>	Spokes No.	Q.TA' RAGGI	12	10		
		Spokes Length	LUNGH. RAGGI	13	<b>L269</b>		
		Spokes Crossing	TIPO INCROCIO	14	Radial (inner) -	radiali (int.)	
		Spokes Tension Kg.	TENSIONE IN KG.	15	105 ± 8%		
<b>FRONT Wheel - LEFT side</b>	<b>ANTERIORE LATO SX</b>	Spokes No.	Q.TA' RAGGI	16	10		
		Spokes Length	LUNGH. RAGGI	17	<b>L269</b>		
		Spokes Crossing	TIPO INCROCIO	18	Radial (inner) -	radiali (int.)	
		Spokes Tension Kg.	TENSIONE IN KG.	19	105 ± 8%		
<b>Spokes &amp; Nipples Specifications</b>	<b>SPECIFICHE RAGGI NIPLES ALTRO</b>	Brand and type	Marca e tipo		Sapim CX-Ray		
		Spokes Material	Materiale Raggi		Stainless steel Inox	Acciaio Inox	
		Spokes Type	TIPO RAGGI INOX	20	Aerodynamic Ø 2 with reduced section	aerodinamico Ø 2 con sezione ridotta	
		Spokes Colour	COLORE RAGGI	21	<b>black</b>	<b>nero</b>	
		Nipples Type	TIPO NIPLES	22	ACI ABS ERGAL L15 T.E.		
		Nipples Material	MATERIALE-COLORE Nipples	23	Ergal Red	Ergal ROSSO	
		Washer	PIASTRINA/ROSETTA	24	ottone - Ø 8 /4,5x 1		
		Nipples Stopper	FRENA FILETTI	25	NO (autolock Nipples)		
<b>RIMS Specifications</b>	<b>SPECIFICHE CERCHIO</b>	Rim Material	MATERIALE	26	<b>carbonio 100%</b>	<b>carbon 100%</b>	
		Rim Sizes	TIPO PROFILO	27	H 40 X 20 diamond-cut (diamantato)		
		Rim Colour	COLORE CERCHIO	28	<b>black carbon</b>	<b>nero carbonio</b>	
		Ø Valve Hole	Ø FORO VALVOLA	29	Ø 6,5 inner//outer	Ø 6,5 interno//esterno	
		Eyelets	BOCCOLE	31	No	No	
		Decoration	DECORAZIONI	32	Sticker	Etichette	
<b>HUBS Specifications</b>	<b>SPECIFICHE MOZZO E CUSCINETTI</b>	Front Hub	MOZZO ANT.	33	FRONT LIGHT C-H-2		
		Rear Hub SH.	MOZZO POST. SH.	34	REAR SH LIGHT C-H-2		
		Rear Hub Campy	MOZZO POST. C.	35	REAR CAMP LIGHT C-H-2		
		O.L.D. Front/Rear Axle	INTERASSE BATTUTA	36	100/130 mm.		
		Spokes Holes Front/rear	FORI POST./ANT.	37	20/20 (std)		
		Hub Colour	COLORE MOZZO	38	<b>BLACK</b>		
		Front Hub Motion	CUSCINETTI 2RS ANT.	39	N.2 Ø10/22x6		
		Rear Hub Motion	CUSCINETTI 2RS POST.	40	N.2 Ø15/28x7		
<b>SHIMANO cassette body</b>	<b>CASSETTE SHIMANO-CUSCINETTI-GHIERE</b>	Material	MATERIALE	41	<b>Ergal anod. Silver</b>	<b>Ergal anod. Silver</b>	
		Shimano	SHIMANO	42	8/9/10S 12/11 teeth	8/9/10S 12/11 denti	
		Cassette Motion	CUSCINETTI 2RS	43	N.2 Ø15/28X7		
		Cog - 12	GHIERA 12 DENTI	44	std Shimano		
		Cog - 11	GHIERA 11 DENTI	45	std Shimano		
		Thightness Torque in Nm	SERRAGGIO GHIERA	46	35/45 Nm		
<b>CAMPY cassette body</b>	<b>CASSETTE CAMPAGNOLO-CUSCINETTI-GHIERE</b>	Material	MATERIALE	48	<b>Ergal anod. Silver</b>	<b>Ergal anod. Silver</b>	
		Campy	CAMPAGNOLO	49	9/10S 12/11 teeth	9/10S 12/11 denti	
		Cassette Seal Ball Bearing	CUSCINETTI 2RS	50	N.2 Ø15/24X5		
		Cog - 12	GHIERA 12 DENTI	51	M27x1 Ø38		
		Cog - 11	GHIERA 11 DENTI	52	M27x1 Ø35		
		Thightness Torque in NM	COPPIA SERRAGGIO	53	35/45 Nm		
<b>Cassette Body replacement</b>	<b>CAMBIO CASSETTA</b>	From Campy to SH.	da Campagnolo a SH.	54	Yes	Si	
		From SH. to Campy	da SH. a Campagnolo	55	Yes	Si	
<b>Quick Release</b>	<b>BLOCCAGGI</b>	O.L.D.	INTERASSE CHIUSURA	56	100/130		
		Colour	COLORE	57	<b>BLACK</b>		
		Model	MODELLO	58	Light Race C		
		Weight	PESO	59	112 gr.		
<b>WHEELS WEIGHT</b>	<b>PESO RUOTE</b>	Front Wheel	RUOTA ANT. Gr.	60	550		
		Rear Wheel	RUOTA POST. GR.	61	710		
		Wheel SET ± 5%	COPPIA RUOTE GR. ± 5%	62	<b>1260</b>		
<b>ASSEMBLYING TOLLERANCE FRONT &amp; REAR</b>	<b>TOLLERANZE RUOTE Anteriore &amp;</b>	Max Roundness	Salto Max	63	<b>0,30 mm.</b>		
		Max obbling	Sbandamento Max	64	<b>0,30 mm.</b>		
		Max Simmetry	Campanatura Max	65	<b>0,50 mm.</b>		
<b>Reccomended assembly</b>	<b>RACCOMANDAZIONI D'USO</b>	Reccomended Tyre	COPERTURA SUGGERITA	72	19 ÷ 25		
		Rim tape - Flap	NASTRO - FLAP	73	-----		
		Max Inflate (Bars)	MAX PRES. CONSENTITA	74	specified Tyre	specifiche copertura	
		Braking pads	PATTINI FRENO	75	special for carbon	speciale per carbonio	