

GIPIEMME 26-08-2011				Modello Ruota \ Wheel model			
wheel technical specifications:				Tecno 716 LIGHT copertoncino			
Scheda Tecnica Ruota modello:				RACE 28"-700C cop. old130 SH.+Camp.20 R			
made in italy - www.gipiemme.com				Rev. 0			
Sizes	MISURE	Tyre	COPERTURA	1	Clincher	Copertoncino	
		Size	MISURA	2	28" - 700C		
		Erto	ERTRO	3	ETRTO 622 - 13,5 DIN		
REAR Wheel - RIGHT side	POSTERIORE LATO DX	Spokes No.	Q.TA' RAGGI	4	10		
		Spokes Length	LUNGH. RAGGI	5	L 262		
		Spokes Crossing	TIPO INCROCIO	6	Cross x 1	Inc. x 1 LIBERO	
		Spokes Tension Kg.	TENSIONE IN KG.	7	140 ± 8%		
					10		
REAR Wheel - LEFT side	POSTERIORE LATO SX	Spokes No.	Q.TA' RAGGI	8	10		
		Spokes Length	LUNGH. RAGGI	9	L 269		
		Spokes Crossing	TIPO INCROCIO	10	Cross x 1	Inc. x 1 LIBERO	
		Spokes Tension Kg.	TENSIONE IN KG.	11	85 ± 8%		
					10		
FRONT Wheel - RIGHT side	ANTERIORE LATO DX	Spokes No.	Q.TA' RAGGI	12	10		
		Spokes Length	LUNGH. RAGGI	13	L 269		
		Spokes Crossing	TIPO INCROCIO	14	Radial (inner) -	radiali (int.)	
		Spokes Tension Kg.	TENSIONE IN KG.	15	105 ± 8%		
					10		
FRONT Wheel - LEFT side	ANTERIORE LATO SX	Spokes No.	Q.TA' RAGGI	16	10		
		Spokes Length	LUNGH. RAGGI	17	L 269		
		Spokes Crossing	TIPO INCROCIO	18	Radial (inner) -	radiali (int.)	
		Spokes Tension Kg.	TENSIONE IN KG.	19	105 ± 8%		
					10		
Spokes & Nipples Specifications	SPECIFICHE RAGGI NIPLES ALTRO	Brand and type	Marca e tipo		Sapim CX-Ray		
		Spokes Material	Materiale Raggi		Stainless steel Inox	Acciaio Inox	
		Spokes Type	TIPO RAGGI INOX	20	Aerodynamic Ø 2 w/ih reduced section	aerodinamico Ø 2 con sezione ridotta	
		Spokes Colour	COLORE RAGGI	21	black	nero	
		Nipples Type	TIPO NIPLES	22	ACI ABS ERGAL L15 T.E.		
		Nipples Material	MATERIALE-COLORE Nipples	23	ERGAL red rosso		
		Washer	PIASTRINA/ROSETTA	24	- Ø 7 / 4,4x0,5 INOX		
		Cross spokes	INCROCIO RAGGI		rubber isolation	gommino isolante	
		Nipples Stopper	FRENA FILETTI	25	NO (autolock Nipples)		
					AL 6082 T6		
RIMS Specifications	SPECIFICHE CERCHIO	Rim Material	MATERIALE	26	H40,5 X 19 / 13,5 welded, diamond-cut (dis.718 saldato, diamantato)		
		Rim Sizes	TIPO PROFILO	27	Anodiz. Black sandblast	Anodiz. Nero sabbiato	
		Rim Colour	COLORE CERCHIO	28	Ø 6.5 / 10		
		Ø Valve Hole	Ø FORO VALVOLA	29	Ø 6.5 / 10		
		Rubber hole valve	GOMMINO FORO VALVOLA		No	No	
		Eyelets	BOCCOLE	31	No	No	
		Decoration	DECORAZIONI	32	Laser + Sticker	Laser + Etichette	
HUBS Specifications	SPECIFICHE MOZZO E CUSCINETTI	Front Hub	MOZZO ANT.	33	FRONT LIGHT C-H-2		
		Rear Hub SH.	MOZZO POST. SH.	34	REAR SH LIGHT C-H-2		
		Rear Hub Campy	MOZZO POST. C.	35	REAR CAMP LIGHT C-H-2		
		O.L.D. Front/Rear Axle	INTERASSE BATTUTA	36	100/130 mm.		
		Spokes Holes Front/rear	FORI POST./ANT.	37	20/20 (std)		
		Hub Colour	COLORE MOZZO	38	BLACK		
		Front Hub Motion	CUSCINETTI 2RS ANT.	39	N.2 Ø10/22x6		
		Rear Hub Motion	CUSCINETTI 2RS POST.	40	N.2 Ø15/28x7		
SHIMANO cassette body	CASSETTE SHIMANO-CUSCINETTI-GHIERE	Material	MATERIALE	41	Ergal anod. Silver	Ergal anod. Silver	
		Shimano	SHIMANO	42	8/9/10S 12/11 teeth	8/9/10S 12/11 denti	
		Cassette Motion	CUSCINETTI 2RS	43	N.2 Ø15/28x7		
		Cog - 12	GHIERA 12 DENTI	44	std Shimano		
		Cog - 11	GHIERA 11 DENTI	45	std Shimano		
		Tightness Torque in Nm	SERRAGGIO GHIERA	46	35/45 Nm		
		Frewheel	VITE	47	-----		
CAMPY cassette body	CASSETTE CAMPAGNOLO-CUSCINETTI-GHIERE	Material	MATERIALE	48	Ergal anod. Silver	Ergal anod. Silver	
		Campy	CAMPAGNOLO	49	9/10S 12/11 teeth	9/10S 12/11 denti	
		Cassette Seal Ball Bearings	CUSCINETTI 2RS	50	N.2 Ø15/24x5		
		Cog - 12	GHIERA 12 DENTI	51	M27x1 Ø38		
		Cog - 11	GHIERA 11 DENTI	52	M27x1 Ø35		
		Tightness Torque in NM	COPPIA SERRAGGIO	53	35/45 Nm		
Cassette Body	CAMBIO CASSETTA	From Campy to SH.	da Campagnolo a SH.	54	Yes	Si	
		From SH. to Campy	da SH. a Campagnolo	55	Yes	Si	
Quick Release	BLOCCAGGI	O.L.D.	INTERASSE CHIUSURA	56	100/130		
		Colour	COLORE	57	Black		
		Model	MODELLO	58	Light Race Y		
		Weight	PESO	59	116 gr.		
WHEELS WEIGHT	PESO RUOTE	Front Wheel	RUOTA ANT. Gr.	60	795		
		Rear Wheel	RUOTA POST. GR.	61	955		
		Wheel SET ± 5%	COPPIA RUOTE GR. ± 5%	62	1750		
ASSEMBLYING TOLLERANCE	TOLLERANZE RUOTE Anteriore &	Max Roundness	Salto Max	63	0,30 mm.		
		Max obbling	Sbandamento Max	64	0,30 mm.		
		Max Symmetry	Campanatura Max	65	0,50 mm.		
Recommended assembly	RACCOMANDEAZIONI D'USO	Recommended Tyre	COPERTURA SUGGERITA	72	19 ± 25		
		Rim tape - Flap	NASTRO - FLAP	73	622 x 16 x 0,6		
		Max Inflate (Bars)	MAX PRES. CONSENTITA	74	Tyre/Copert. 19 ► 10 Bar - Tyre/Copert. 25 ► 9 Bar		
		Braking pads	PATTINI FRENO	75	standard		